

Container Station

Edit and Recreate Container

1 Select Image 2 Configure Container 3 Summary

Image Configuration

Mode: Basic mode Advanced mode

Registry:

Image:

Try pulling the image from the registry before creating the container.

- 1. Data that is not stored in bind mounts or volumes will be discarded.
- 2. Using images other than the original may cause compatibility issues. Make sure that your data is supported between different images and versions. Contact the image provider before proceeding.

Container Station

Edit and Recreate Container

Advanced Settings

Commands

Networks

Environments

Labels

Storage

Runtime

Resources

Networks

Network mode: Default (NAT) Custom

Interface:

Hostname:

MAC address:

Default web URL port:

Use a static IP address

IP address: . . .

Subnet mask: . . .

Gateway: . . .

Environments

Labels

Storage

Runtime

Resources

Variable: PHP_URL

Value: https://www.php.net/distributions/php-8.2.15.tar.xz

Variable: PHP_VERSION

Value: 8.2.15

Variable: WATCHTOWER_DOCKER_SOCKET_PATH

Value: /Container/container-station-data/lib/docker/var/run/docker.s



Advanced Settings

Commands

Networks

Environments

Labels

Storage

Runtime

Resources

Storage

Storage Mapping

Add Volume | ▾

Host: /Container/container-station-data/lib/docker/var/run/docker.sock

Container: /var/run/docker.sock

RW RO

Host: /Container/nextcloud_aio

Container: /mnt/docker-aio-config

RW RO